

Matriz LED BICOLOR 8x8

Características:

- Matriz de LEDs de 8x8
- Diámetro de cada LED: 5.00mm
- Color: Rojo y Verde
- **Electrical Parameters**
- Note:
 1. Luminous intensity tolerance is $\pm 10\%$;
 2. Dominant Emission Wavelength tolerance is $\pm 5\%$.
- **Package Dimensio**



Chip Material: AlGaInP / GaAs Ultra Bright Red LED Chip

ABSOLUTE MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$)



PARAMETER	SYMBOL	MAXIMUM RATING	UNIT
Power Dissipation	P_D	72	mW
Peak Forward Current (1/10 Duty Cycle, 0.1 Ms Pulse Width)	I_{PEAK}	90	mA
DC Forward Current	I_F	30	mA
Reverse Voltage	V_R	5	V
Operating Temperature Range	T_A	-40°C to +85°C	
Storage Temperature Range	T_{STG}	-40°C to +85°C	
Solder temperature 1/16 inch below seating plane for 3 seconds at 260°C			

ELECTRICAL OPTICAL CHARACTER AND CURVES (Ta = 25°C)

PARAMETER	SYMBOL	MIN	TYP	MAX	UNIT	LOCATION	TEST CONDITION
Forward Voltage	V _F	-	2.10	2.40	V	Per Chip	I _F = 20mA
Luminous Intensity	I _v	58.0	68.0	74.0	mcd	Per Chip	I _F = 20mA
Peak Emission Wavelength	λ _p	-	645	-	nm	Per Chip	I _F = 20mA
Dominant Emission Wavelength	λ _d	626	631	636	nm	Per Chip	I _F = 20mA
Spectral Line Half-Width	Δλ _{1/2}	-	20	-	nm	Per Chip	I _F = 20mA
Capacitance	C	-	95	-	pF	Per Chip	V _F = 0V; f = 1MHz
Reverse Current	I _R	-	-	10	uA	Per Chip	V _R = 5V



Ánodo común (BRGND)



Cátodo común (ARGND)

